

# Ka-98V

# iNetVu®

by C-COM Satellite Systems Inc.

## TECHNICAL SPECIFICATIONS

The iNetVu® Ka-98V Drive-Away Antenna is a 98 cm auto-acquire satellite antenna system which can be mounted on the roof of a vehicle for direct broadband access over any configured satellite. The system works seamlessly with the iNetVu® 7024C Controller providing fast satellite acquisition within minutes, anytime anywhere.



### Features

- One-Piece high surface accuracy, off set feed, steel reflector
- Heavy duty feed arm capable of supporting up to 5kg (10 lbs) RF Electronics (LNB & BUC) or transceiver
- Designed to work with the iNetVu® 7024C Controller
- Works seamlessly with the world's emerging commercial ViaSat/KA-SAT satellite Surfbeam II modems
- Auto beam select on KA-SAT Tooway services
- 2 Axis motorization
- Supports manual control when required
- One button, auto-pointing controller acquires any Ka-band satellite within 2 minutes
- Field upgradable to Ku-band
- Locates satellites using the most advanced satellite acquisition methods
- Supports Skyware Global 98 cm Ka antenna and 4W transceiver
- Available with pod option
- Standard 2 year warranty

**ViaSat**

Type approved for KA-SAT

**eutelsat**

Type approved for KA-SAT



### Application Versatility

If you operate in Ka-band, the Ka-98V system is easily configured to provide instant access to satellite communications for any application that requires reliable and/or remote connectivity in a rugged environment. This next generation mobile Ka terminal delivers affordable broadband Internet services (High-speed access, video & Voice over IP, file transfer, e-mail or web browsing). Ideally suited for industries such as Oil & Gas Exploration, Military Communications, Disaster Management, SNG, Emergency Communications Backup, Cellular Backhaul and many others.

[www.itbroadcast.eu](http://www.itbroadcast.eu)

+361 452 1055 | [broadcast@infoteka.hu](mailto:broadcast@infoteka.hu)

**BROADCAST** **INFOTEKA**  
**SOFTWARE**

Copyright © 2013 Infotéka Software Kft.

# Ka-98V

# iNetVu®

by C-COM Satellite Systems Inc.

## TECHNICAL SPECIFICATIONS

### Mechanical

Reflector	98 cm Elliptical Antenna, offset feed
Platform Geometry	Elevation over Azimuth
Deployment Sensors	GPS antenna Compass $\pm 2^\circ$ Tilt sensor $\pm 0.1^\circ$
Azimuth	Full 360° in overlapping 200° sectors
Elevation	0-90°
Elevation Deploy Speed	Variable 2°/sec typ.
Azimuth Deploy Speed	Variable 15°/sec Max., 10°/sec typ.
Peaking Speed	0,1°/sec

### Environmental

Survival	
Wind Deployed	160 km/h (100 mph)
Wind Stowed	225 km/h (140 mph)
Temperature	-40°C to 65°C (-40°F to 150°F)
Operational	
Wind	72 km/h (45 mph)
Temperature	-30°C to 55°C (-22°F to 130°F)
Thermal Test:	MIL-STD-810F, Method 501.4, High/Low Temperatures
Vibration Test:	MIL-STD-810F, Annex A, Category 4, Truck/Trailer/Tracked
Shock Test:	IEC 60068-2-27

### Electrical

Rx & Tx Cable	2 RG6 cables - 10 m (33 ft) each	
Control Cables		
Standard	10 m (33 ft) Ext. Cable	
Optional	up to 60 m (200 ft) available	
	<b>Receive</b>	<b>Transmit</b>
Frequency (GHz)	18,30 – 20,20	28,10 – 30,00
Feed Interface (Circular)	RG6	RG6
Midband Gain (+/-0.2 dBi)	43.50 @19.75 GHz	46.60 @29.75 GHz
Antenna Noise Temp. (K)	30° EL= 62 Max.	
Sidelobe Envelope Co-Pol (dBi)		
100λ / D < Ø < 20°	29 - 25 Log Ø	
20° < Ø < 26.3°	-3.5	
26.3° < Ø < 48°	32-25 Log Ø	
48° < Ø < 180°	-10 (typical)	
VSWR	1.3:1	

### RF interface

Radio Mounting	Feed Arm
Coaxial	RG6U from Transceiver to Base Connector

### Physical

Mounting Plate	L: 161 cm (63.5") W: 45 cm (17.7")
Stowed Reflector Ext. Dims (without reflector pod)	L: 164.8 cm (64.9") W: 100 cm (39.5") H: 29 cm (11.5")
Stowed Reflector Ext. Dims (with reflector pod)	L: 178.8 cm (70.4") W: 113 cm (44.5") H: 29 cm (11.5")
Deployed Height	151 cm (59.5")
Platform Weight	54 kg (119 lbs)
Reflector back cover	2.27 kg (5 lbs)
Pod alone	6.8 kg (15 lbs)
Total Platform Weight (without reflector pod)	56.3 kg (124 lbs)
Total Platform Weight (with reflector pod)	63 kg (139 lbs)

### Motors

Electrical Interface	24VDC 8 Amp (Max.)
----------------------	--------------------

### Shipping Weights & Dimensions

Crate	183 cm x 109 cm x 66 cm (72" x 43" x 26"), 52 kg (114 lbs)
Platform	54 kg (119 lbs)
7024C Controller	6 kg (13 lbs)
Cables	5 kg (11 lbs)
Total weight without pod:	117 kg (258 lbs)
Pod inside shipping box:	33 cm x 127 cm x 127 cm (13" x 50" x 50"), 16.1 kg (35.5 lbs)
Transportable Case includes Platform (Optional):	
Platform Case	183 cm x 109 cm x 47 cm (72" x 43" x 18.5"), 133.5 kg (294 lbs)

[www.itbroadcast.eu](http://www.itbroadcast.eu)

+361 452 1055 | [broadcast@infoteka.hu](mailto:broadcast@infoteka.hu)

BROADCAST INFOTEKA SOFTWARE

Copyright © 2013 Infoteka Software Kft.