

Ka-75V

iNetVu®

by C-COM Satellite Systems Inc.

TECHNICAL SPECIFICATIONS

The iNetVu® Ka-75V Drive-Away Antenna is a 75 cm auto-acquire satellite antenna system which can be mounted on the roof of a vehicle for direct broadband access over any configured satellite. The system works seamlessly with the iNetVu® 7024C Controller providing fast satellite acquisition within minutes, anytime anywhere.

"Approved for use on ExedeSM Ka Service by VIASAT and on KA-SAT NEWSPOTTER NEWSGATHERING service by Eutelsat"



Features

- One-Piece, high surface accuracy, offset feed, steel reflector
- Heavy duty feed arm capable of supporting up to 5kg (10lbs)
- Ka transceiver
- Designed to work with the iNetVu® 7024C Controller
- Works seamlessly with the world's emerging commercial
- VIASAT / KA-SAT satellite Surfbeam II/PRO Nomadic modems
- 2 Axis motorization
- Supports manual control when required
- One button, auto-pointing controller acquires Ka-band satellite within 2 minutes
- Locates satellites using the most advanced satellite acquisition methods
- Supports Skyware Global 75 cm Ka antenna
- Standard 2 year warranty



Application Versatility

If you operate in Ka-band, the Ka-75V system is easily configured to provide instant access to satellite communications for any application that requires reliable and/or remote connectivity in a rugged environment. This next generation mobile Ka terminal delivers affordable broadband Internet services (High-speed access, video & Voice over IP, file transfer, e-mail or web browsing). Ideally suited for industries such as Oil & Gas Exploration, Military Communications, Disaster Management, SNG, Emergency Communications Backup, Cellular Backhaul and many others.

www.itbroadcast.eu
+361 452 1055 | broadcast@infoteka.hu

BROADCAST **INFOTEKA**
SOFTWARE

Copyright © 2013 Infotéka Software Kft.

Ka-75V

iNetVu®

by C-COM Satellite Systems Inc.

TECHNICAL SPECIFICATIONS

Mechanical

Reflector	75cm Elliptical Antenna, offset feed
Platform Geometry	Elevation over Azimuth
Deployment Sensors	GPS antenna Compass $\pm 2^\circ$ Tilt sensor $\pm 0.1^\circ$
Azimuth	Full 360° in overlapping 200° sectors
Elevation	0-90°
Elevation Deploy Speed	Variable, 10°/sec typ.
Azimuth Deploy Speed	Variable 5°/sec typ.
Peaking Speed	0,1°/sec

Environmental

Survival	
Wind Deployed	160 km/h (100 mph)
Wind Stowed	225 km/h (140 mph)
Temperature	-40°C to 65°C (-40°F to 150°F)
Operational	
Wind	72 km/h (45 mph)
Temperature	-30°C to 55°C (-22°F to 130°F)
Thermal Test:	MIL-STD-810F, Method 501.4, High/Low Temperatures
Vibration Test:	MIL-STD-810F, Annex A, Category 4, Truck/Trailer/Tracked
Shock Test:	IEC 60068-2-27

Electrical

Rx & Tx Cable	2 RG6 cables - 10 m (33 ft) each	
Control Cables		
Standard	10 m (33 ft) Ext. Cable	
Optional	up to 60 m (200 ft) available	
	Receive	Transmit
Frequency (GHz)	18,30 – 20,20	28,10 – 30,00
Feed Interface (Circular)	RG6	RG6
Nominal G/T	17,5 dB/K	
Nominal EIRP	48,4 dBW	

RF interface

Radio Mounting	Feed Arm
Coaxial	RG6U from Transceiver to Base Connector

Physical

Mounting Plate	L: 131 cm (51.6") W: 45 cm (17.7")
Stowed Reflector Ext. Dims	L: 145 cm (57") W: 76 cm (29.9") H: 29 cm (11.5")
Deployed Height	122 cm (48")
Platform Weight	52 kg (115 lbs)

Motors

Electrical Interface	műholdkar
Koax	RG6U

Shipping Weights & Dimensions

Crate	183 cm x 109 cm x 66 cm (72" x 43" x 26"), 52 kg (114 lbs)
Platform	52 kg (115 lbs)
7024C Controller	6 kg (13 lbs)
Cables	5 kg (11 lbs)
Total weight	115 kg (253 lbs)
Transportable Case	155 cm x 84 cm x 34 cm (61" x 33" x 13.5"), 107 kg (235 lbs)
Option: Base Case	